



Gulf ATF DX II D

Automatic Transmission Fluid

Product Description

Gulf ATF DX II D is an automatic transmission fluid for automatic transmissions in older vehicles specifying use of DEXRON® II D quality fluids. The high quality base oils and special additive system used in this oil provide resistance to oxidation, better frictional properties, good low temperature fluidity, improved seal compatibility & wear protection. It exceeds the performance requirements of General Motors DEXRON® II D specification and provides excellent driving experience in a variety of driving conditions.

Features & Benefits

- Good thermo-oxidative stability minimises formation of lacquer, sludge & deposits and keeps transmission clean
- Controlled frictional characteristics helps in consistent and smooth shifts in a variety of driving conditions
- Improved antiwear technology protects critical transmission parts against wear
- Extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss
- Enhanced Low temperature fluidity assist in good cold start performance
- Provides better protection against rust and corrosion
- Compatibility with all common seal materials

Applications

- Recommended for all vehicles of General Motors requiring DEXRON®-II D quality fluids.
- Also recommended for power steering units, certain manual transmissions and hydraulic systems where such type of fluids are required

Specifications, Approvals & Typical Properties

Meets the following Specifications		
General Motors DEXRON® IID, Ford MERCON®		X
ZF TE-ML 02F, 03D, 04D, 09, 11B, 11A, 14A, 17C		X
Voith 55.6335, MAN 339 Z1 & V1, MAN 339 Z2 & V2		X
Allison C-4, CAT TO-2		X
Mercedes-Benz MB 236.1 & MB 236.5H, Daimler 13C100		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	7.4
Viscosity Index	D 2270	169
Flash Point, °C	D 92	170
Pour Point, °C	D 97	-48
Brookfield Viscosity @ -40 °C, cP	D 2983	25794
Density @ 15°C, Kg/l	D 1298	0.860

DEXRON® is a registered trademark of General Motors Corporation.

MERCON® is a registered trademark of Ford Motor Company

October 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com