



# Gulf EP Lubricant SY

## Synthetic heavy-duty industrial gear oil

### Product Description

**Gulf EP Lubricant SY** series are premium quality synthetic heavy duty industrial gear oils offering outstanding lubrication performance and load carrying capacity under severe operating conditions including shock loading. These are formulated from Polyalphaolefin (PAO) synthetic base stocks having exceptional oxidation resistance and thermal properties and excellent low temperature fluidity. The combination of naturally high viscosity index base stocks coupled with carefully selected additive technology provides excellent protection against scuffing and resistance against micro pitting fatigue under wide operating temperature range.

### Features & Benefits

- Outstanding load carrying capability and micro-pitting performance protects gears against scuffing and wear leading to enhanced equipment life and reduced maintenance costs
- High viscosity index base stocks provide excellent low temperature fluidity and effective lubrication over a wide temperature range
- Superior thermo-oxidative stability provides enhanced system cleanliness and enables longer service intervals
- Low traction and enhanced lubricity helps provide extra energy efficiency
- Excellent resistance to rust and corrosion protection and good demulsibility ensures trouble free operation at high temperatures and applications encountering water contamination
- Good seal and paint compatibility with a wide variety of seals and paints

### Applications

- Heavy-duty industrial enclosed gear boxes operating under severe conditions like high load, extreme temperatures and wide temperature ranges
- Filled for life systems
- Bearing and circulation systems where high temperatures are encountered

### Specifications, Approvals & Typical Properties

ISO Viscosity Grade		68	100	150	220	320	460	680	1000
<b>Meets the following Specifications</b>									
DIN 51517 Part 3, AISE(US Steel)224		X	X	X	X	X	X	X	X
ISO 12925-1 Type CKD, David Brown S1.53.101(E), AGMA 9005 E-02		X	X	X	X	X	X	X	X
<b>Has the following Approval</b>									
Siemens Revision 15 for Flender gear units				X	X	X	X	X	
<b>Typical Properties</b>									
Test Parameters	ASTM Method	Typical Values							
Viscosity @ 40 °C, cSt	D 445	67.7	100.2	150.8	223.4	326.5	462.7	685.1	951.8
Viscosity Index	D 2270	152	155	158	148	153	159	168	160
Flash Point, °C	D 92	276	242	246	249	252	252	255	266
Pour Point, °C	D 97	-36	-42	-39	-42	-39	-39	-36	-24
Density @ 15°C, Kg/l	D 1298	0.847	0.849	0.851	0.857	0.859	0.860	0.861	0.856
FZG, fail load stage	DIN 51354 Part II	-	>12	>12	>12	>12	>12	>12	>12
Rust Test	D 665A/B	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion	D 130	1a	1a	1a	1a	1a	1a	1a	1a
Emulsion Test 30 minutes max @ 82 °C	D 1401	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass

December 2016

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)