



Gulf Formula G

Passenger Car Motor Oil

Product Description

Gulf Formula G is a high performance passenger car motor oil formulated from finest quality synthetic base stocks and high performance additive technology. It is developed for turbocharged, high output gasoline and diesel engines of passenger cars, SUVs, light vans and trucks. It has been designed to deliver long service life and minimise deposits in engine and turbocharger components to ensure rated engine power and torque.

Features & Benefits

- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended oil & engine life
- Improved fuel economy and extended drain intervals reduce the cost of ownership
- Excellent low temperature fluidity aids quick cold start and provides wear protection at start-up
- Outstanding Stay-in-Grade performance ensures reliable lubrication even at higher load and operating temperatures
- Superior antiwear technology provides excellent wear protection under all conditions
- Active cleaning agents ensure maximum engine cleanliness

Applications

- Recommended for all light duty vehicles including high performance, turbo-charged, multi valve, direct injection gasoline and diesel engines of passenger cars, SUVs, light vans and trucks meeting up to Euro 4/ Euro 5 emission norms and requiring conventional type lubricants (not catalyst compatible type)
- The SAE 5W-30 viscosity grade exceed the requirements of most European, North American and Japanese passenger cars including gasoline powered racing cars

Specifications, Approvals & Typical Properties

| Meets the following Specifications | | 5W-30 |
|--|-------------|----------------|
| ACEA A3/B4, MB 229.3H, Renault RN0710 | | X |
| Has the following Approvals | | |
| API SL | | X |
| Approved under VW Standard 502 00 and 505 00 | | X |
| Typical Properties | | |
| Test Parameters | ASTM Method | Typical Values |
| Viscosity @ 100 °C, cSt | D445 | 12.2 |
| Viscosity Index | D 2270 | 165 |
| Flash Point, °C | D 92 | 226 |
| Pour Point, °C | D 97 | -42 |
| TBN, mg KOH/g | D 2896 | 10.9 |
| Density @ 15°C, Kg/l | D 1298 | 0.8564 |

April 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com