



Gulf Formula PCX

Catalyst Compatible Synthetic Passenger Car Motor Oil

Product Description

Gulf Formula PCX is a catalyst compatible synthetic passenger car motor oil offering fuel economy benefits. It helps maintain the efficiency of emission reduction systems and extends its life. It is compatible with exhaust after treatment devices such as Diesel Particulate Filter (DPF) and Gasoline Three Way Catalyst (TWC). It meets the service fill requirements of PSA Peugeot Citroën vehicles and vehicles requiring ACEA C2 type of oils.

Features & Benefits

- Latest mid SAPS additive technology prolongs life of exhaust after treatment devices such as DPF & TWC
- Outstanding thermo-oxidative stability resists oil degradation and thus facilitates extended oil change intervals
- Active cleaning agents reduce deposits & sludge and keeps engine clean
- Enhanced friction reduction properties provide improved fuel economy
- Excellent antiwear properties provides superior wear protection
- Reliable viscosity control ensures wear protection across wide temperature range and provides low temperature fluidity to aid quick cold start

Applications

- Passenger cars, SUV's and light vans of PSA Peugeot and Citroën requiring oils meeting PSA B71 2312 specifications
- Modern high performance gasoline and diesel engines in passenger cars and light duty vehicles fitted with DPF and TWC requiring catalyst compatible fuel economy oils meeting ACEA C2 specifications

Specifications, Approvals & Typical Properties

Meets the following Specifications		0W-30
ACEA C2		X
PSA B71 2312		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	9.6
Viscosity Index	D 2270	175
Flash Point, °C	D 92	228
Pour Point, °C	D 97	-36
Density @ 15°C, Kg/l	D 1298	0.847
Sulfated Ash, % wt	D 874	0.50
Phosphorus, % wt	D 4047/ICP	0.078

September 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com