



# Gulf Gear TDL

## Total Driveline Lubricant

### Product Description

**Gulf Gear TDL** series are thermally stable total driveline gear lubricants designed to meet the severe requirements of drivetrains of light and heavy duty commercial vehicles. These are blended from premium quality base stocks and advanced performance additives to provide excellent protection to drivetrain components, improved gear shifting and enhanced synchroniser protection. These oils provide reliable protection against thermal and oxidation degradation, rust & corrosion and good low temperature fluidity.

### Features & Benefits

- Unique additive technology allows the use of a single lubricant in rear axles, synchronised and non-synchronised manual transmissions and therefore helps in rationalisation of products
- Exceptional thermo-oxidative stability and load bearing characteristics help in extending the life of the driveline components and the oil
- Effective rust and corrosion protection, especially to copper and its alloys reduces wear, extends synchroniser life and improves shifting performance
- Good low temperature fluidity reduces wear and provides easy start-up
- Good anti-foam properties ensure film strength for effective lubrication
- Superior seal compatibility minimises leakage and reduces chance of contamination

### Applications

- Rear axles, synchronised and non-synchronised manual transmissions requiring a single lubricant
- Drivetrains requiring oils meeting MAN M 3343 Type M (SAE 80W-90, SAE 85W-140) and Scania STO 1:1 G for gearboxes & 1:0 for axles (SAE 80W-90 only)
- On-road and Off-highway transmission applications requiring lubricants meeting any of these specs:
  - API GL-4/GL-5    ◦ API MT-1    ◦ MIL-PRF-2105E
  - SAE J 2360       ◦ Mack GO-J    ◦ Renault
  - Eaton            ◦ DAF            ◦ Volvo
- Not recommended for automatic transmissions and limited-slip differentials

### Specifications, Approvals & Typical Properties

Meets the following Specifications		80W-90	85W-140
API GL-5, API MT-1, MIL-PRF-2105E, SAE J 2360, MAN M 3343 Type M		X	X
ZF TE-ML-05A, 07A, 08, 12E, 16C/D, 19B, DAF, MACK GO-J, Eaton*		X	X
ZF TE-ML-16D, Iveco (Axle)			X
API GL-4/GL-5, Volvo 97310, MB 235.0, Renault*, Iveco*		X	
Has the following Approvals			
MAN 342 Typ M2, MAN 341 Typ Z2, Scania STO 1:0 for axles and Scania STO 1:1 G for gearboxes		X	
Approval according to ZF Lubricant Classes TE-ML 02B, TE-ML 05A, TE-ML 12L, TE-ML 12M, TE-ML 16B, TE-ML 17H, TE-ML 19B, TE-ML 21A (ZF Approval Number: ZF000780)		X	
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity at 100 °C, cSt	D 445	15.2	27.04
Viscosity Index	D 2270	101	99
Flash Point, °C	D 92	206	214
Pour Point, °C	D 97	-30	-18
Density @ 15°C, kg/l	D 1298	0.896	0.901

\* - Where either API GL-5, API MT-1 or MIL-PRF-2105E axle lubricants are recommended for use. Refer service manual  
July 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)