

Gulf Gear VX

High Performance Semi-Synthetic Gear Oil

Product Description

Gulf Gear VX 75W-90 is a semi-synthetic gear lubricant designed for improved fuel economy in passenger cars using manual transmissions. It is blended from carefully selected base fluids and proven additive technology system to provide unmatched protection for extended durability of driveline components and enhanced fuel efficiency. Gulf Gear VX 75W-90 provides excellent protection to gears and bearings and is also compatible with various components within the transmission. It also supports extension of drain interval.

Features & Benefits

- Superior lubricating properties provide improved fuel economy compared to conventional gear oil.
- Usage of proven additive technology with optimised friction levels ensures very good gear engagement with a variety of synchroniser materials.
- Provides effective protection against rust and corrosion to gear components.
- · Provides excellent wear protection over wide range of temperatures.
- Outstanding low temperature fluidity ensures in smoother gear shift performance.
- Exceptional shear stability helps retaining viscosity and film strength to protect against wear even under severe operating conditions.

Applications

- Suitable for transmissions requiring VW 501 50 quality oils
- Recommended for use in manual gearboxes, transaxles, transfer boxes and final drives where an API GL4 lubricant is specified.
- Not recommended for automatic transmissions.

Specifications, Approvals & Typical Properties

Meets the following Specifications API GL-4		75W-90
		X
VW 501 50		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	14.05
Viscosity Index	D 2270	166
Brookfield Viscosity @ -40 0C, cP	D 2983	Pass
Flash Point, °C	D 92	210
Pour Point, °C	D 97	-48
Density @ 15°C, kg/l	D 1298	0.880

May 2013

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language

version shall prevail. www.gulfoilltd.com