



# Gulf MAX Ultra GDI

## Semi-Synthetic Passenger Car Motor Oil

### Product Description

**Gulf MAX Ultra GDI** series is most advanced semi-synthetic passenger car motor oil specially developed for the modern turbocharged Gasoline Direct Injection (GDI) engines in passenger cars, sport utility vehicles, vans, and light-duty trucks. These are formulated with special additives and high quality base stocks to provide protection against Low Speed Pre-Ignition (LSPI) and timing chain wear issues generally observed in latest turbocharged GDI engines. provides excellent protection against wear, deposits & sludge build-up and help to protect engines even while operating on ethanol containing fuels up to E85. These oils meet the highest API quality API SP. Further, SAE 5W-30 also meets ILSAC GF-6A requirements which helps in improving & retaining fuel economy.

### Features & Benefits

- Latest additive technology coupled with synthetic base fluids makes these oils robust and provides improved engine deposit protection, wear and turbocharger protection
- Protects turbocharged Gasoline Direct Injection (GDI) engines against Low Speed Pre-Ignition (LSPI) and Timing chain wear
- Excellent low temperature fluidity coupled with viscosity retention at higher temperature offers reliable protection over a wide temperature range
- Special friction modifier in SAE 5W-30 helps improve & retain fuel economy
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution
- Offers emission system durability and seal compatibility

### Applications

- North American, European & Japanese high output gasoline engines in passenger cars, sport utility vehicles, vans, and light-duty trucks where API SP, SN Plus, ILSAC GF-6A and / or API SN, API SM, API SL quality oils are specified (backward compatible)
- Passenger cars and Light Duty Vehicles running on gasoline and ethanol-containing fuels up to E85>
- Suitable for modern turbocharged Gasoline Direct Injection (GDI) engines where Low Speed Pre-Ignition (LSPI) and Timing chain wear protection is required

### Specifications, Approvals & Typical Properties

Has the Following Approvals		5W-30	5W-40	10W-40
API SP (Resource Conserving), ILSAC GF-6A		X		
API SP, API SN Plus		X	X	X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	10.8	13.3	14.7
Viscosity Index	D 2270	160	166	155
Flash Point, °C	D 92	232	234	236
Pour Point, °C	D 97	-45	-42	-39
TBN, mg KOH/g	D 2896	7.1	7.1	7.1
Density @ 15°C, Kg/l	D 1298	0.856	0.854	0.870
CCS, cP (°C)	D 5293	5793 (-30)	6476 (-30)	6300 (-25)
MRV, cP (°C)	D 4684	20800 (-35)	28400 (-35)	27800 (-30)
HTHS, cP	D 4683	3.2	3.7	4.1

February 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)