

Gulf MAX

Passenger Car Motor Oil

Product Description

Gulf MAX is a high quality passenger car motor oil developed for modern, high-output, multi valve, turbocharged & supercharged gasoline powered passenger cars and diesel powered light duty vehicles. All the grades are developed to exceed the performance requirements of API SL.

Features & Benefits

- Better thermo-oxidative stability minimises deposits & sludge build-up facilitating extended oil life
- · Active cleaning agents provide engine cleanliness
- Excellent antiwear property minimises engine wear and thereby reduces maintenance cost
- · Good low temperature fluidity assists in easy cold starts
- Stay-in-grade performance ensures reliable lubrication even at higher load & operating temperatures

Applications

- Recommended for high performance, multi valve, turbocharged & supercharged gasoline powered passenger cars and diesel powered light duty vehicles requiring API SL & API CF quality oils
- SAE 40 viscosity grades are recommended for use in older vehicles where use of single-grade motor oil of API SL or any previous "S" category is recommended

Specifications, Approvals & Typical Properties

Meets the following Specifications		40	10W-30	10W-40	15W-40	20W-50	
API CF				Х	Х	Х	
Has the following Approvals							
API SL		Х	Χ	Х	Х	Х	
Typical Properties							
Test Parameters	ASTM Method		Typical Values				
Viscosity @ 100 °C, cSt	D 445	14.4	11.10	14.40	14.60	18.40	
Viscosity Index	D 2270	101	143	154	130	121	
Flash Point, °C	D 92	266	218	224	224	226	
Pour Point, °C	D 97	-18	-39	-33	-27	-27	
TBN, mg KOH/g	D 2896	7.0	6.60	6.80	7.40	7.80	
Density@15°C, Kg/l	D 1298	0.885	0.858	0.885	0.893	0.896	
Sulphated Ash, %wt	D 874	0.93	0.83	0.82	0.90	0.90	

May 2022