Gulf Pride 4T Plus

Premium 4-Stroke Motorcycle Oil

Product Description

Gulf Pride 4T Plus is a premium quality 4-stroke gasoline engine oil developed specifically to meet the special requirements of the latest high-performance air cooled 4-stroke motorcycles. It is blended from superior quality high viscosity index base oils and specially selected performance additives to provide excellent protection for engine, gearbox and wet clutch used in 4-stroke motorcycles. SAE 10W-30 & 10W-40 are semi-synthetic. It provides high degree of reliability even under severe operating conditions. This oil exceeds the JASO MA2 specification for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers.

Features & Benefits

- Outstanding thermo-oxidative stability minimises high temperature deposit formation and controls oil thickening facilitating extended engine and oil life.
- Exceptional antiwear properties protect vital engine and gear components leading to reduced maintenance costs.
- Optimised frictional properties eliminate wet clutch slippage leading to increased power / fuel economy and improved drivability.
- Unique combination of detergents and dispersants provide excellent control on piston deposits leading to faster heat dissipation and longer engine life.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Exceptional low volatility characteristics reduce oil consumption and hydrocarbon pollution.
- Effective rust and corrosion inhibition property ensures longer life of critical engine components.

Applications

- Recommended for new generation 4-stroke gasoline engines in high performance motorcycles of all leading global manufacturers.

Specifications, Approvals & Typical Properties

Meets the following Specifications		**10W-30**	**10W-40**	**20W-40**	**20W-50**
API SL		**X**	**X**	**X**	**X**
JASO MA2		**X**	**X**	**X**	**X**
Typical Properties					
Test Parameters	**ASTM Method**	**Typical Values**			
Viscosity @ 100 ºC, cSt	D 445	10.7	13.5	14.4	18.7
Viscosity Index	D 2270	146	153	120	127
Flash Point, ºC	D 92	234	236	246	243
Pour Point, ºC	D 97	-33	-36	-33	-24
TBN, mg KOH/g	D 2896	9.3	5.5	7.9	8.1
Density @ 15ºC, Kg/l	D 1298	0.867	0.864	0.876	0.894
Sulphated Ash, %wt	D 874	1.07	0.78	1.00	1.13

September 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com