



Gulf Pride 4T Ultra Plus

Superior Performance 4-Stroke

Motorcycle Oil

Product Description

Gulf Pride 4T Ultra Plus is a superior quality 4-stroke motorcycle oil developed specifically to meet the special requirements of the latest high performance air cooled 4-stroke motorcycles. These are blended from superior quality base oils and specially selected performance additives to provide excellent engine, gearbox and wet clutch protection. These oils exceed the JASO MA2 specification for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers.

Features & Benefits

- Outstanding thermo-oxidative stability minimises high temperature deposit formation facilitating extended engine and oil life
- Exceptional antiwear properties protect engine and gear components for reduced maintenance costs
- Optimised frictional properties helps minimise clutch slippage for smooth drivability & fuel economy
- It provides excellent control on piston deposits leading to faster heat dissipation and longer engine life
- Excellent shear stability helps retain viscosity for improved wear protection
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- SAE 10W-30, 10W-40, 20W-40 & 20W-50 viscosity grades are recommended for latest 4-stroke gasoline engines in high performance motorcycles of all leading global manufacturers
- SAE 5W-30 product recommended for specific motorcycle models recommending such type of product

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30	10W-30	10W-40	20W-40	20W-50
API SN		X	X	X	X	X
JASO MA2				X		X
Has the following Approvals						
JASO MA2 on-file registration		X	X		X	
Typical Properties						
Test Parameters	ASTM Method	Typical Values				
Viscosity @ 100 °C, cSt	D 445	11.1	11.1	14.3	15.2	18.0
Viscosity Index	D 2270	161	142	156	116	122
Flash Point, °C	D 92	232	236	240	242	242
Pour Point, °C	D 97	-42	-33	-33	-30	-30
TBN, mg KOH/g	D 2896	6.9	8.9	7.6	8.9	7.4
Density @ 15°C, Kg/l	D 1298	0.852	0.860	0.858	0.882	0.885
Sulphated Ash, %wt	D 874	0.8	1.0	0.8	1.0	1.0

March 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com