



# Gulf Pride Scooter Plus

## Advanced 4-Stroke Scooter Engine Oil

### Product Description

**Gulf Pride Scooter Plus** series is a superior performance 4-stroke scooter engine oils for modern scooters with automatic transmission and dry clutch. Scooter engines being compact and enclosed, operate at elevated temperatures and hence need specially formulated oils to provide adequate protection against wear & deposits. It ensures smoother ride even in severe city stop & go riding conditions. The unique friction modifier in these oils helps reduce engine friction for improved fuel economy benefits as compared to conventional motorcycle oils. These products meets/exceeds the requirements of the API SN and JASO MB for 4-stroke scooter engine oils.

### Features & Benefits

- Unique friction modifiers oil reduces the engine friction to provide improved fuel economy
- Excellent thermo-oxidative stability protects against engine deposits & oil thickening
- Advanced detergents helps keep engine parts cleaner to provide longer engine life
- Superior anti-wear additives protect highly stressed engine components to minimise maintenance cost
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

### Applications

- Recommended for modern scooters with automatic transmissions and dry clutch
- Suitable for air cooled 4-stroke engines where API SN and JASO MB quality oil is required

*Note: Not recommended for motorcycles with wet clutch. For motorcycle oils, please contact Gulf Oil representative.*

### Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-30	10W-40	20W-40
API SN		X	X	X
JASO MB		X		X
Has the following On File Status				
JASO MB on-file registration			X	
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	10.8	14.8	14.3
Viscosity Index	D 2270	149	153	114
Flash Point, °C	D 92	242	242	236
Pour Point, °C	D 97	-39	-36	-33
TBN, mg KOH/g	D 2896	8.6	7.3	8.6
Density @ 15°C, Kg/l	D 1298	0.859	0.867	0.882
Sulphated Ash, %wt	D 874	0.8	0.8	0.8

January 2023

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)