

# Gulf Quench

#### Normal speed quenching oil

## **Product Description**

**Gulf Quench** series are normal speed quenching oils developed for heat treatment of ferrous metals in a wide variety of quenching operations. These oils are formulated from highly refined paraffinic oils to provide superior ageing stability. They possess good inherent thermal and oxidation stability offering long service life with minimal deposit formation. Their low volatility characteristics reduce oil loss from vaporisation and the uniform heat dissipation property minimises stress and metal distortion ensuring uniform hardness. These oils are available in two viscosity grades and are recommended for normal speed quenching of ferrous metals such as carbon steel, gray iron and alloy steels.

## Features & Benefits

- · Good inherent thermal and oxidation stability minimises deposit formation and viscosity increase
- Superior ageing stability leads to extended service life and reduced downtime
- Lower drag-out losses and reduced clean-up costs minimise operational costs
- Imparts good surface finish
- Uniform heat dissipation property minimises stress and metal distortion
- Low volatility reduces oil loss from vaporisation

## Applications

• Normal speed quenching of ferrous metals such as carbon steel, gray iron and alloy steels

#### **Specifications, Approvals & Typical Properties**

Gulf Quench		22	32	44	65
Typical Properties					
Test Parameters	ASTM Method	Test Values			
Viscosity @ 40 °C, cSt	D 445	21.9	31.8	44.0	64.8
Viscosity Index	D 2270	98	95	97	98
Flash Point, ºC	D 92	188	208	218	220
Pour Point, °C	D 97	-21	-18	-18	-18
Density @ 15°C, Kg/l	D 1298	0.861	0.868	0.875	0.882
GM Quench Speed, seconds	D 3520	23.3	24.1	25.5	24.0

April 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language

version shall prevail. www.gulfoilltd.com