



Gulf Super Duty LE Plus

Commercial Vehicle Engine Oil

Product Description

Gulf Super Duty LE Plus is extra high performance heavy-duty diesel engine oil specifically developed for use in modern, low emission diesel engines, including those fitted with Exhaust Gas Re-circulation (EGR) systems. This product offers exceptional protection and extended life to diesel engines operating on low or high Sulphur diesel. It is blended from selected base stocks and new generation performance additives.

Features & Benefits

- High oxidation stability reduces sludge build up & viscosity increase to facilitate long drain intervals
- Improved detergency reduces deposits and enhances engine cleanliness
- Better soot handling capacity helps control oil thickening and wear
- Effective anti wear properties protect engine parts against wear to extend engine life and reduce maintenance costs
- Good corrosion inhibition properties provide protection against rust and corrosion

Applications

- Turbocharged and naturally aspirated diesel engines of major North American, European and Japanese engine manufacturers
- On highway light and heavy-duty trucking including high speed-high load service and short haul pick-up/delivery van
- For Engines fitted with exhaust gas recirculation system also for engines with open crankcase ventilation
- Heavy duty diesel engines used in mining, construction, agriculture and other off road applications where API CI-4 type of Engine oils are recommended

Specifications, Approvals & Typical Properties

| Meets the following Specifications | | 15W-40 | 20W-50 |
|--|-------------|----------------|--------|
| API CI-4 | | | X |
| API CI-4/ SJ, ACEA A3/B3-16, MB 229.1 | | X | |
| Daimler 15B110 | | X | X |
| MTU Oil Category 2, Cummins CES 20076, Deutz II-18 | | X | X |
| Typical Properties | | | |
| Test Parameters | ASTM Method | Typical Values | |
| Viscosity at 100 °C, cSt | D 445 | 14.2 | 18.9 |
| Viscosity Index | D 2270 | 139 | 124 |
| Flash Point, °C | D 92 | 222 | 234 |
| Pour Point, °C | D 97 | -30 | -24 |
| TBN, mg KOH/g | D 2896 | 8.4 | 8.5 |
| Density @ 15°C, Kg/l | D 1298 | 0.8745 | 0.8864 |
| Sulphated Ash, wt% | D 874 | 1.18 | 1.18 |

July 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com