



Gulf Super Duty VLE

Commercial Vehicle Engine Oil

Product Description

Gulf Super Duty VLE is super high performance diesel engine oil for use in all modern low emission, turbocharged & naturally aspirated diesel engines. It is blended from selected base stocks and advanced additives to provide utmost engine protection and extended oil drain intervals. The product has been specifically developed to meet the requirements of engines conforming to Euro 3 and Euro 2 emission norms and also meets the stringent requirements of Volvo and other major global engine manufacturers.

Features & Benefits

- Excellent thermo-oxidative stability controls deposits & viscosity increase facilitating longer drain intervals
- Advanced detergency reduces deposits and enhances engine cleanliness
- Better soot handling capability leads to control of soot induced oil thickening and wear
- Exceptional anti wear properties protect critical engine components resulting in extended engine life and reduced maintenance costs

Applications

- Turbocharged and naturally aspirated low emission diesel engines of all major global engine manufacturers
- On-highway light and heavy duty trucking including high speed-high load service and short haul pick-up/delivery van
- Heavy duty diesel engines used in mining, construction, agriculture and other off-highway applications

Specifications, Approvals & Typical Properties

Meets the following Specifications		15W-40
ACEA E7		X
MAN M 3275, Cummins CES 20076/20077/20078, MTU Oil Category 2		X
Has the following Approvals		
API CI-4/SL		X
Daimler Truck Fluid Release 15B110		X
Volvo VDS-3/ Mack EO-N/ Renault VI RLD-2 approval		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	13.9
Viscosity Index	D 2270	132
Flash Point, °C	D 92	237
Pour Point, °C	D 97	-42
TBN, mg KOH/g	D 2896	10.3
Density @ 15°C, Kg/l	D 1298	0.895
Sulphated Ash, %wt	D 874	1.42

July 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com