Gulf Superfleet Professional Long Drain

Synthetic Technology for Heavy Duty Diesel Engines

Product Description

Gulf Superfleet Professional Long Drain oils are synthetic heavy duty diesel engine oils exclusively designed for the new generation, high performance, low emission engines used in severe on-highway applications. The advanced formulation with Tri-guard technology helps engines to fight against wear, and deposit build-up, and neutralises harmful acidic combustion byproducts preventing corrosion. Thus, it maximizes oil drain interval and reduces maintenance cost and Total Cost of Ownership to today's modern fleet. The latest low SAPS (Sulphated Ash, Phosphorus, Sulphur) additive chemistry used in these oils facilitates in maintaining the efficiency of the emission reduction systems such as Diesel Particulate Filter (DPF), which is used by some vehicle manufacturers to meet Euro IV, Euro V and forthcoming Euro VI emission requirements.

Features & Benefits

- Excellent deposit, wear & corrosion protection provides extended drain interval
- Excellent antiwear technology provides exceptional wear protection facilitating extended engine life
- Superior thermo-oxidative stability facilitates extended drain intervals & engine life
- Superior low temperature fluidity aids cold start and protects against wear at start-up
- Advance low SAPS additive technology protects after treatment devices
- Superior shear stability reduces viscosity breakdown and oil consumption

Applications

- Recommended for highly rated diesel engines meeting Euro IV, Euro V, Euro VI and earlier emission norms and running under very severe conditions like extended drain intervals
- Suitable for EGR engines with or without particulate filters and for engines fitted with SCR NOx reduction systems
- Strongly recommended for engines fitted with particulate filters and is designed for vehicles running on low sulphur diesel fuel (Max. 50 ppm)
- Suitable for application in commercial vehicle gas engines

Specifications, Approvals & Typical Properties

Meets the following Specifications		**10W-40**
ACEA E7/ E8/ E11, API CI-4, JASO DH-2		**X**
Cummins CES 20076/20077, MAN M 3477, MAN M 3271-1, MTU Oil Category 3.1		**X**
Deutz DQC IV-18 LA, DAF Extended Drain, CAT ECF-1a		**X**
Has the following Approvals		
Daimler Truck Fluid Release 15C110		**X**
Volvo VDS-3/ Mack EO-N/ Renault Trucks RLD-2 approval		**X**
Typical Properties		
Test Parameters	**ASTM Method**	**Typical Values**
Viscosity @ 100 ºC, cSt	D 445	15.0
Viscosity Index	D 2270	155
Flash Point, ºC	D 92	232
Pour Point, ºC	D 97	-36
TBN, mg KOH/g	D 2896	10.2
Density @ 15ºC, Kg/l	D 1298	0.8644
Sulphated Ash, wt%	D 874	1.0
Phosphorus, wt%	D 4047/ICP	0.075
Sulphur, wt%	D 129/ICP	0.22

November 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com