



# Gulf Superfleet Special QC

## Commercial Vehicle Engine Oil

### Product Description

**Gulf Superfleet Special QC SAE 15W-40** is an extra high performance diesel engine oil that provides superior performance and long service potential in high output, high-speed turbocharged diesel engines operating under severe conditions. It is blended from highly refined base stocks and carefully selected additives to provide excellent control of oil thickening, high temperature deposits and inhibits oxidation and corrosion. It meets the requirements of major European heavy-duty diesel engine manufacturers.

### Features & Benefits

- Excellent thermo-oxidative stability controls deposits & viscosity increase
- Exceptional anti wear properties protect critical engine components to extend engine life and reduce maintenance costs
- Advanced detergency reduces deposits and enhances engine cleanliness to provide extended engine life
- Better high temperature – high shear stability protects against bore polishing

### Applications

- Turbocharged and naturally aspirated low emission diesel engines of major European & American engine manufacturers
- On highway light and heavy duty trucking including high speed-high load service and short haul pick-up/delivery van
- Heavy duty diesel engines used in mining, construction, agriculture and other off highway applications

### Specifications, Approvals & Typical Properties

Meets the following Specifications		15W-40
MB 228.3, MAN M 3275, Mack EO-M		X
Cummins 20071, 20072		X
Volvo VDS-2		X
Has the following Approvals		
API CH-4		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	14.50
Viscosity Index	D 2270	135
Flash Point, °C	D 92	230
Pour Point, °C	D 97	-27
TBN, mg KOH/g	D 2896	9.80
Density @ 15°C, Kg/l	D 1298	0.89
Sulphated Ash, wt%	D 874	1.35

October 2019

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)