



Gulf Superfleet XLD

Extra High Performance Diesel (XHPD)

Engine Oil

Product Description

Gulf Superfleet XLD 10W-40 is extra high performance diesel engine oil developed to provide outstanding protection to modern high performance diesel engines used in severe applications. It is formulated with high performance base stocks and advanced additives to provide excellent lubrication and 'Extra Long Drain' intervals. Gulf Superfleet XLD 10W-40 is designed for use in most demanding heavy duty diesel engines meeting Euro IV emission standards.

Features & Benefits

- Superior protection against bore polishing ensures longer engine life
- Exceptional deposit control leading to cleaner engine and thereby reduced maintenance costs
- Extended TBN reserve enables prolonged drain interval capability
- High viscosity index facilitates smooth operation over a wide temperature range
- Excellent low temperature fluidity enables easy starting at cold ambient temperatures and offers wear protection at start-up
- High shear stability ensures viscosity control, wear protection and lower oil consumption
- Outstanding detergency provides protection against high temperature deposits

Applications

- Recommended for use in all low emission turbo charged and naturally aspirated heavy-duty diesel engines meeting Euro IV emission standards manufactured by North American, European and Japanese manufacturers requiring such quality oils
- Suitable for on road applications including light and heavy duty highway and city applications, mining, construction, agriculture and other off road applications
- Depending upon the specific engine model and service conditions, oil change intervals of 100,000 km can easily be achieved

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-40
ACEA E4, E7		X
Scania LDF-2, Mack EO-M Plus		X
Cummins CES 20077/78, MB 228.5, MAN M 3277		X
DAF Extended Drains, Renault Trucks RXD, Volvo VDS-3, Mack EO-N, Renault VI RLD-2		X
Has the following Approval		
API CI-4		X
MTU Oil Category 3		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	14.58
Viscosity Index	D 2270	154
Flash Point, °C	D 92	214
Pour Point, °C	D 97	-30
TBN, mg KOH/g	D 2896	12.7
Density @ 15°C, Kg/l	D 1298	0.874
Sulphated Ash, wt%	D 874	1.7

April 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com