



Gulf Superfleet XLE

Extra High Performance Diesel (XHPD)

Engine Oil - Low SAPS

Product Description

Gulf Superfleet XLE oils are extra high performance semi synthetic diesel engine oils exclusively designed for the new generation, high performance, low emission engines used in severe on-highway applications. These oils are formulated using the highest quality base fluids that provide outstanding high temperature viscosity retention, low temperature fluidity, volatility control and fuel economy improvement. The latest low SAPS (Sulphated Ash, Phosphorus, Sulphur) additive chemistry used in these oils facilitates in maintaining the efficiency of the emission reduction systems such as Diesel Particulate Filter (DPF), which is used by some vehicle manufacturers to meet Euro 4, Euro 5 and forthcoming Euro 6 emission requirements. Gulf Superfleet XLE series are also suitable for application in HD gas engines.

Features & Benefits

- Excellent thermo-oxidative stability provides protection against high temperature deposits, sludge build-up and oil thickening
- Superior shear stability reduces viscosity breakdown and oil consumption
- Excellent low temperature fluidity enables easy pumpability and circulation at low ambient temperatures and therefore enables wear protection at start-up
- The advanced low SAPS additive technology protects after treatment devices from deposits and deterioration of catalysts
- Excellent antiwear property and high temperature-high shear viscosity provide protection against engine wear & bore polishing facilitating extended engine life

Applications

- Recommended for highly rated diesel engines meeting Euro 4, Euro 5, Euro 6 and earlier emission norms and running under very severe conditions like extended drain intervals
- Suitable for EGR engines with or without particulate filters and for engines fitted with SCR NOx reduction systems
- Strongly recommended for engines fitted with particulate filters and is designed for vehicles running on low sulphur diesel fuel (Max. 50 ppm)
- Suitable for application in HD gas engines

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-30	10W-40
ACEA E6-16; API CI-4		X	X
Deutz DQC III-05, MAN M 3477; M 3271-1, MTU Oil Category 3.1		X	X
Volvo VDS-3/ Mack EO-N/ Renault VI RLD-2		X	
Daimler 15C110			X
Has the following Approvals			
Volvo VDS-3/ Mack EO-N/ Renault VI RLD-2 approval			X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	12.1	14.6
Viscosity Index	D 2270	145	156
Flash Point, °C	D 92	232	230
Pour Point, °C	D 97	-39	-39
TBN, mg KOH/g	D 2896	10	8.6
Density @ 15°C, Kg/l	D 1298	0.863	0.861
Sulphated Ash, wt%	D 874	0.90	0.98
Phosphorus, wt%	D 4047/ICP	0.074	0.078
Sulphur, wt%	D 129/ICP	0.232	0.290

July 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com