



# Gulf Supreme Duty ULE

## Premium heavy duty diesel engine oil for Ultra low emission engines

### Product Description

**Gulf Supreme Duty ULE** is premium performance heavy duty diesel engine oil specially developed for use in ultra low emission engines meeting the latest US and European emission standards. This oil addresses the unique needs of the latest engines and enhances the life of exhaust after treatment devices. It is formulated with state-of-the-art additive technology and severely hydroprocessed base oils to provide excellent performance and overall protection having a potential to offer extended drain intervals. It meets the performance requirements of API CK-4 service category. It is also backward compatible for the use in older engines requiring API CJ-4 and below quality oils.

### Features & Benefits

- Outstanding thermal and oxidative stability reduces low-temperature sludge build-up, high-temperature deposits and oil thickening
- Excellent soot handling capability minimises soot related viscosity increase and leads to longer engine/oil life
- Superior shear stability maintains viscosity in severe service conditions and leads to improved wear protection.
- Exceptional TBN retention resists harmful effects of corrosive exhaust gases and extends oil life
- Low ash content reduces particulate build-up in Diesel Particulate Filter (DPF) and enhances its life.

### Applications

- Latest high performance low emission heavy duty diesel engines including those equipped with DPF and Exhaust Gas Recirculation (EGR) and meeting the latest US and European emission standards.
- On-highway vehicles and off-highway equipment operating in severe low speed/heavy load conditions using either low (500 ppm) or ultra low (15 ppm) sulphur fuels.
- Suitable for the use in earlier engine models requiring API CJ-4 and below quality oils.

### Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-30	10W-40	15W-40
ACEA E9, API CJ-4, CES 20086, DDC 93K222		X		X
ACEA E9, API CJ-4, MB 228.31, DQC III-10 LA, MTU Type 2.1, CES 20081, DDC 93K218, Cat ECF-3,			X	
Has the following Approvals				
API CK-4		X	X	X
Volvo VDS-4.5; Mack EOS-4.5; Renault VI RLD-3		X	X	X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	12.0	15.4	15.6
Viscosity Index	D 2270	143	156	133
Flash Point, °C	D 92	230	221	230
Pour Point, °C	D 97	-33	-39	-30
Density @ 15°C, Kg/l	D 1298	0.887	0.887	0.862
Phosphorus, %wt	D 4927	0.11	0.11	0.11
Sulphated Ash, %wt	D 874	1.0	0.99	0.96

March 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)