



# Gulf Supreme Duty XLE

*Extra high performance diesel engine oil for low emission engines*

## Product Description

**Gulf Supreme Duty XLE** series are extra high performance diesel engine oils specially developed for use in modern, high-output, low emission engines meeting US 2007 on-highway exhaust emission standards. These oils not only address the unique needs of these new engines and enhances the life of exhaust after treatment devices but also provides improved protection to older engines. These are formulated with state-of-the-art additive technology and severely hydroprocessed base oils to provide outstanding performance and overall protection. It exceeds the performance requirements of API CJ-4 and major global OEMs.

## Features & Benefits

- Outstanding thermal and oxidative stability reduces low-temperature sludge build-up, high-temperature deposits and oil thickening
- Excellent soot handling minimizes soot related viscosity increase and leads to longer engine/oil life
- Outstanding corrosive and abrasive wear protection extends life of engine components
- Exceptional TBN retention resists harmful effects of corrosive exhaust gases and extends oil life
- Low ash content reduces particulate build-up in Diesel Particulate Filter (DPF) and enhances its life

## Applications

- Latest high performance low emission engines including those equipped with DPF and Exhaust Gas Recirculation (EGR) and meeting US 2007 on-highway exhaust emission standards
- On-highway vehicles and off-highway equipments operating in severe low speed/heavy load conditions using either low (500 ppm) or ultra low (15 ppm) sulphur fuels
- High performance gasoline engines and mixed fleet operations requiring oils meeting API CI-4 PLUS, CI-4, CH-4, CG-4 CF-4, SN (5W-40 & 10W-40), SM, SL and SJ performance levels

## Specifications, Approvals & Typical Properties

Meets the following Specifications	5W-40	10W-30	10W-40	15W-40	
ACEA E9, Cummins CES 20081	X	X	X	X	
MAN M3575-1, MB 228.31, Volvo VDS-4, RVI RLD-3, Mack EO-O PP, DDC DFS93K218	X		X		
MTU Oil Category 2.1	X	X	X		
MAN M 3575		X		X	
CAT ECF 3, ECF 2 and ECF1a		X	X	X	
Deutz III-10 LA		X	X		
Has the following Approvals					
API CJ-4/SN	X		X		
API CJ-4, Volvo VDS-4/ Mack EO-O PP/ Renault VI RLD-3 approval		X		X	
MB-Approval 228.31, MTU Oil Category 2.1				X	
Typical Properties					
Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	15.1	11.8	14.3	15.0
Viscosity Index	D 2270	169	142	155	138
Flash Point, °C	D 92	230	230	232	236
Pour Point, °C	D 97	-36	-33	-39	-36
TBN, mg KOH/g	D 2896	10.4	9.4	8.1	8.6
Density @ 15°C, Kg/l	D 1298	0.857	0.871	0.855	0.876
Sulphated Ash, %wt	D 874	0.94	0.99	0.98	0.99
Phosphorus, %wt	D 4047/ICP	0.115	0.114	0.113	0.114
Sulphur, %wt	D 129/ICP	0.30	0.39	0.360	0.39

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)



2022

May

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)