



Gulf Syntac 4T Plus

Premium Fully Synthetic 4-Stroke Motorcycle Oil

Product Description

Gulf Syntac 4T Plus series are premium fully synthetic, 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air cooled 4-stroke motorcycles. It is specially formulated from premium quality base stocks and advanced additive technology to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles and helps minimize internal motorcycle engine friction, providing improved performance and efficiency. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions. It is suitable for wide range of ambient temperatures. These oil meets the specifications of API SN, JASO MA2 and the requirements of leading global 4-stroke motorcycle manufacturers.

Features & Benefits

- Excellent thermo-oxidative stability minimises deposits and controls oil thickening facilitating extended engine and oil life
- Exceptional antiwear properties protect vital engine and gear components leading to reduced maintenance costs
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability
- Special detergents/ dispersants used in this oil ensure cleaner pistons leading to faster heat dissipation and longer engine life
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection
- The special formula helps minimize internal motorcycle engine friction, providing improved performance and efficiency.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- Recommended for powerful 4-stroke gasoline engines in high performance motorcycles of leading global manufacturers operating in wide range of ambient temperatures

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-40	10W-40
API SN		X	X
Has the following On File Status			
JASO MA2		X	X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	14.3	14.3
Viscosity Index	D 2270	168	158
Flash Point, °C	D 92	242	238
Pour Point, °C	D 97	-42	-36
TBN, mg KOH/g	D 2896	7.5	7.6
Density @ 15°C, Kg/l	D 1298	0.859	0.865
Sulphated Ash, %wt	D 874	0.80	0.80

November 2020

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.