



# Gulf Syntac Superbike 4T

## Fully Synthetic 4-Stroke Motorcycle Oil

### Product Description

**Gulf Syntac Superbike 4T** are fully synthetic, 4-stroke gasoline engine oils developed specifically to meet the special requirements of latest high performance air cooled 4-stroke racing bikes with wet clutch system. These are blended with advanced additive technology and synthetic base stock (PAO and ester) to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles. These provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions. These oils are available in SAE 5W-40, SAE 10W-40, SAE 10W-50 and SAE 15W-50 viscosity grades and meets the specifications of API SN and JASO MA2.

### Features & Benefits

- Excellent thermo-oxidative stability minimizes deposits and controls oil thickening facilitating extended engine and oil life
- Controlled frictional properties eliminate clutch slippage leading to increased power and improves drivability
- Exceptional antiwear properties protect vital engine and gear components under extreme riding conditions
- Special detergents/ dispersants used in this oil ensure cleaner pistons leading to faster heat dissipation and longer engine life
- Excellent shear stability maintains viscosity under high temperature high shear environment and provides improved wear protection
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

### Applications

- High performance racing bikes with wet clutch system requiring such type of oils
- Also recommended for advanced 4-stroke gasoline engines in high performance motorcycles of leading global manufacturers operating in wide range of ambient temperatures

### Specifications, Approvals & Typical Properties

Meets the following Specification		5W-40	10W-40	10W-50	15W-50
API SN		X	X	X	X
Has the following On File Status					
JASO MA2		X	X	X	X
Typical Properties					
Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	14.6	15.1	19.0	19.1
Viscosity Index	D 2270	160	184	160	150
Flash Point, °C	D 92	260	228	262	266
Pour Point, °C	D 97	-48	-48	-45	-42
Density @ 15°C, Kg/l	D 1298	0.854	0.871	0.852	0.857

May 2019

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.