



Gulf XHD

Commercial Vehicle Engine Oil

Product Description

Gulf XHD series are diesel engine oils developed to meet the requirements of a variety of naturally aspirated diesel engines operating under different conditions. It is blended from highly refined base stocks and chosen additives to provide reliable protection to engines operating under various environments. It is suitable for use in a wide range of on and off-highway applications where such type of lubricant is recommended.

Features & Benefits

- Effective antiwear characteristics protect engine components
- Good detergency characteristics ensure cleaner engine
- Better corrosion inhibition properties offer protection against rust and corrosion

Applications

- Older generation diesel engines and gasoline engines of all leading engine manufacturers where such performance level oil is recommended
- On-highway applications including light and heavy duty trucking
- Heavy-duty diesel engines used in mining, construction, agriculture and other off-highway road applications where such type of oil is recommended

Specifications, Approvals & Typical Properties

Meets the following specifications		30	40	50	20W-40
API CC/SC		X	X	X	X
Typical Properties					
Test Parameters	ASTM Method	Typical values			
Viscosity @ 100 °C, cSt	D 445	11.4	14.6	18.3	14.26
Viscosity Index	D 2270	98	97	98	113
Flash Point, °C	D 92	238	246	248	246
Pour Point, °C	D 97	-15	-12	-12	-24
TBN, mg KOH/g	D 2896	3.2	3.2	3.5	3.55
Density @ 15°C, Kg/l	D 1298	0.891	0.900	0.900	0.897
Sulphated Ash, %wt	D 874	0.44	0.44	0.49	0.49

April 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com