



Gulf Gear LD

Supreme Performance Heavy Duty Axle Oil

Product Description

Gulf Gear LD is a supreme performance heavy duty axle oil specifically designed to meet the requirements of highly loaded axles used in latest generation commercial vehicles. It is formulated from high quality base stocks and latest additive technology for commercial vehicle rear axle applications to provide extended oil drain periods, enhanced load carrying, improved fuel economy and thermal stability combined with seals performance. The product meets Daimler's latest MB 235.20 axle oil specification and the requirements of major OEMs for transmission oils.

Features & Benefits

- Excellent load carrying capabilities and thermo-oxidative stability facilitate longer component life and extended oil drain interval.
- Stable viscometrics provide optimal film thickness, component protection, low temperature oil flow and maintain efficiency over extended period.
- Effective rust and corrosion protection reduces wear and extends component life
- Good anti-foam properties ensure film strength for effective lubrication
- Improved dynamic seal performance prevents leakages and deposits even in extended duration.

Applications

- Exclusively developed for Mercedes-Benz HL-6 axles and also for applications requiring axle oil meeting MB 235.0 and MB 235.6 specification for enhanced performance.
- Heavy duty on-highway vehicles and off-highway equipment transmissions, axles and final drives where API GL-5, API MT-1 or SAE J 2360 quality oils are specified
- Other heavy-duty applications involving hypoid and other gears operating under severe conditions like high speed/shock load and/or low speed/high torque
- Not suitable for automatic transmissions.

Specifications, Approvals & Typical Properties

Meets the following Specifications		80W-90
API GL-5, API MT-1, MIL-PRF-2105E, SAE J 2360		X
Scania STO 1:0, MACK GO-J, MAN 341 Typ GA1		X
ZF TE-ML 07A, 16C, 16D		X
Has the following Approvals		
Approval according to ZF Lubricant Classes TE-ML 05A, TE-ML 12L, TE-ML 12M, TE-ML 16B, TE-ML 17B, TE-ML 19B, TE-ML 21A (ZF Approval Number: ZF001950)		X
MAN 342 Typ M3, DTFR 12B110 (Previously known as MB 235.20)		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	14.40
Viscosity Index	D 2270	102
Flash Point, °C	D 92	210
Pour Point, °C	D 97	-30
Density @ 15°C, kg/l	D 1298	0.8944

June 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.