



# Gulf Gear SY

## High Performance Heavy Duty Axle Oil

### Product Description

**Gulf Gear SY** is high performance heavy duty axle oil for hypoid gears in axle drives of commercial vehicles, off-highway equipment and passenger cars. It is blended from severely hydro-cracked base oils and robust performance additives to provide excellent protection to gear components even during high working loads and heavy impacts. Its excellent extreme pressure properties impart high load-carrying capability to provide reliable protection to gear components in applications where extreme pressure and shock loading are encountered. It provides effective protection against oxidation degradation, rust & corrosion and long service life. The product meets the requirements of Volvo Construction Equipment GO 101.

### Features & Benefits

- Excellent extreme pressure and antiwear properties shields against wear under various operating conditions leading to enhanced equipment durability and lower maintenance costs
- Very Good oxidation stability minimises sludge and deposit formation facilitating longer component life and oil service intervals.
- Effective rust and corrosion protection reduces wear and extends component life
- Good low temperature fluidity facilitates ease of operation at low ambient temperatures
- Good anti-foam properties ensure film strength for effective lubrication
- Excellent seal compatibility helps minimise leakages and reduce chances of contamination

### Applications

- Axles with hypoid gears in heavy duty vehicles where API GL-5 quality oils are specified
- Off-highway equipment in construction, mining and agriculture
- On-road passenger cars, light and heavy duty trucks, buses and vans
- Other heavy-duty applications involving hypoid and other gears operating under severe conditions like high speed/shock load, high speed/low torque and/or low speed/high torque
- Not suitable for automatic transmissions

### Specifications, Approvals & Typical Properties

Meets the following Specifications		75W-90
API GL-5, US MIL-L-2105D		X
Volvo Construction Equipment VCE 1273,16 (Transmission Oil 97316, GO 101)		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	15.1
Viscosity Index	D 2270	181
Flash Point, °C	D 92	204
Pour Point, °C	D 97	-42
Density @ 15°C, Kg/l	D 1298	0.87

September 2009

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.