



Gulf PowerTrac Scooter

Full Synthetic 4-Stroke Scooter Engine Oil

Product Description

Gulf PowerTrac Scooter is a full synthetic, 4-stroke scooter engine oil for modern high performance scooters with automatic transmission and dry clutch. It exceeds the most demanding lubrication requirements of modern 4-stroke scooter engines and provides excellent engine protection over wide range of operating conditions for enhanced performance & reliability. It helps reduce engine friction for improved fuel economy benefits as compared to conventional motorcycle oils. It exceeds the requirements of the API SN and JASO MB for 4-stroke scooter engine oils.

Features & Benefits

- Unique friction modifiers reduce engine friction for improved fuel economy.
- Exceptional thermo-oxidative stability protects against engine deposits & oil thickening.
- Superior anti-wear properties protect vital engine components for reliable performance.
- Excellent detergency helps keep engine parts cleaner.
- Effective rust and corrosion inhibition property ensures longer engine life.

Applications

- Recommended for advanced 4-stroke engines of high performance scooters of leading global manufacturers with automatic transmissions and dry clutch.
- Suitable for air cooled 4-stroke engines where API SN and JASO MB quality oil is required.
- Suitable for applications in a wide range of ambient temperatures.

Note: Not recommended for motorcycles with wet clutch. For motorcycle oils, please contact Gulf Oil representative.

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-40
API SN		X
JASO MB		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	14.0
Viscosity Index	D 2270	171
Flash Point, °C	D 92	236
Pour Point, °C	D 97	-30
TBN, mg KOH/g	D 2896	7.3
Density @ 15°C, Kg/l	D 1298	0.8533
Sulphated Ash, %wt	D 874	0.87

August 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com