



# Gulf Superfleet Special

## Commercial Vehicle Engine Oil

### Product Description

**Gulf Superfleet Special** is high performance heavy-duty diesel engine oil developed to meet the performance requirements of modern turbocharged and naturally aspirated diesel engines operating under severe conditions. It is blended from highly refined base stocks and proven multifunctional additives to provide excellent performance and long drain intervals. The product meets the requirements of an array of heavy duty diesel engines used in variety of applications.

### Features & Benefits

- High oxidation stability reduces sludge build up & viscosity increase to facilitate long drain intervals
- Improved detergency reduces deposits and enhances engine cleanliness
- Good dispersancy ensures soot dispersion to control oil thickening and wear
- Effective anti wear properties protects critical engine components to extend engine life and reduce maintenance costs
- Better high temperature-high shear stability protects against bore polishing

### Applications

- Turbocharged and naturally aspirated diesel engines of all major global engine manufacturers meeting Euro 2 and Euro 1 emission norms
- On-highway light and heavy duty trucking including high speed-high load service and short haul pick-up/delivery van
- Heavy duty diesel engines used in mining, construction, agriculture and other off-highway applications

### Specifications, Approvals & Typical Properties

Meets the following Specifications		SAE 15W-40	SAE 20W-50
API CG-4/CF		X	X
DTFR 15B110 (Previously known as MB 228.3)		X	X
MTU DDC Oil Category 2		X	X
Volvo VDS		X	X
MAN M 3275		X	X
Mack EO-L		X	X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity at 100 °C, cSt	D 445	14.50	18.5
Viscosity Index	D 2270	135	123
Flash Point, °C	D 92	220	222
Pour Point, °C	D 97	-27	-27
TBN, mg KOH/g	D 2896	10.00	10.00
Density @ 15°C, Kg/l	D 1298	0.895	0.897
Sulphated Ash, wt%	D 874	1.45	1.45

May 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.