



Gulf Syngear

Synthetic Total Driveline Lubricant

Product Description

Gulf Syngear series are fully synthetic thermally stable total driveline gear lubricants designed to meet the demanding requirements of light duty and heavy duty commercial vehicles and off-highway equipment operating in most severe operating conditions. These are blended from synthetic base fluids and advanced technology additive system to provide unmatched protection for extended durability of driveline components. These oils possess outstanding load-carrying capability and high viscosity index to provide effective lubrication in applications encountering high-speed/shock load and low-speed/high torque conditions and wide temperature ranges. These oils possess excellent low temperature fluidity and offer improved fuel economy.

Features & Benefits

- Unique additive technology allows the use of a single lubricant in rear axles, synchronised and non-synchronised manual transmissions and therefore helps in rationalisation of products.
- Exceptional thermo-oxidative stability and load bearing characteristics help in extending the life of the driveline components and the oil.
- Effective rust and corrosion protection, especially to copper and its alloys reduces wear, extends synchroniser life and improves shifting performance.
- Outstanding low temperature fluidity reduces wear at start up and provides smoother shifting at low ambient temperatures.
- Exceptional shear stability helps in retaining viscosity and film strength to protect against wear even under severe operating conditions.
- Superior frictional properties provide improved fuel economy and smoother shiftability.

Applications

- Rear axles, synchronised and non-synchronised manual transmissions requiring single lubricant.
- Drivetrains requiring oils meeting MAN M 3343 Type S or Scania STO 2:0 A FS, STO 1:1 G (75W-90) and STO 2:0 A (75W-140).
- On-road and Off-highway transmission applications requiring lubricants meeting any of these specs:
 - API GL-5 ◦ API MT-1 ◦ MIL-PRF-2105E
 - SAE J 2360 ◦ Mack GO-J ◦ MIL-L-2105 D
- Not recommended for automatic transmissions and limited-slip differentials.

Specifications, Approvals & Typical Properties

Refer next page

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.



| Meets the following Specifications | | 75W-90 | 75W-140 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|----------------|---------|
| API GL-5, API MT-1, MIL-PRF-2105E, MIL-L-2105 D, SAE J 2360, Mack GO-J | | x | x |
| ZF TE-ML- 07A, 08, ArvinMeritor O-76N, DAF*, Eaton*, Iveco* | | x | |
| Has the following Approvals | | | |
| MAN 342 Typ S1, MAN 341 Typ Z2, DTFR 12B140 (Previously known as MB 235.8) | | x | |
| Approval according to ZF Lubricant Classes ZF TE-ML-02B, TE-ML-02B, TE-ML-05A, TE-ML-12L, TE-ML-12N, TE-ML-16F, TE-ML-17B, TE-ML-19C, TE-ML-21A (ZF Approval Number: ZF000863) | | x | |
| Scania STO 1:1 G for gearboxes and Scania STO 2:0 A FS for axles | | x | |
| Scania STO 2:0 A (Scania axle oil requirement that gives high fuel efficiency and extended oil drain interval) | | | x |
| Typical Properties | | | |
| Test Parameters | ASTM Method | Typical Values | |
| Viscosity at 100 °C, cSt | D 445 | 15.00 | 25.00 |
| Viscosity Index | D 2270 | 154 | 168 |
| Flash Point, °C | D 92 | 158 | 160 |
| Pour Point, °C | D 97 | -51 | -45 |
| Density @ 15°C, kg/l | D 1298 | 0.863 | 0.867 |

* - Where either API GL-5 or MIL-PRF-2105E axle lubricants are recommended for use.

July 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com