



Gulf TEC Plus

Passenger Car Motor Oil

Product Description

Gulf TEC Plus is a high performance semi-synthetic passenger car motor oil designed to provide optimum performance in high-output, multi valve, turbocharged & supercharged gasoline and diesel engines of passenger cars, vans, SUVs and light trucks. Its specially chosen additive technology enables reliable performance across different operating conditions while meeting the requirements of leading passenger car manufacturers and global industry standards.

Features & Benefits

- Superior thermo-oxidative stability helps minimise deposits, sludge build-up, reduces oil thickening, to facilitate extended oil life and ensure engine cleanliness
- Excellent antiwear technology minimises engine wear and offers reduced maintenance cost
- Improved detergency protects against engine deposits to ensure reliable performance
- Superior dispersants provide excellent control over soot induced oil thickening
- Good low temperature fluidity assists in easy cold starts and low temperature wear protection

Applications

- Modern high performance, multi valve, turbocharged & supercharged engines of passenger cars, vans, SUVs & light trucks operating under city stop-and-go, high-speed and/or high load conditions
- SAE 10W-40 grade is developed for high performance gasoline and diesel engines of passenger cars, vans, SUV's & light trucks where API SN quality and/or ACEA A3/B4 oils are specified

Note: Not suitable for vehicles meeting emission standards beyond Euro 4. For such applications, please contact Gulf representative.

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-30	10W-40	20W-50
ACEA A3/B4			X	
MB 229.1, API CF		X		X
MB 229.3, MB 226.5			X	
VW 501 01 / 505 00			X	
Renault RN0710 /0700			X	
Has the following Approvals				
API SN			X	
API SL		X		X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	12.0	15.0	17.5
Viscosity Index	D 2270	142	153	122
Flash Point, °C	D 92	218	232	224
Pour Point, °C	D 97	-39	-33	-24
TBN, mg KOH/g	D 2896	8.2	10.4	8.0
Density @ 15°C, Kg/l	D 1298	0.875	0.873	0.886
Sulphated Ash, %wt	D 874	-	1.31	0.95

May 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.