



Gulfmar MX

Marine Engine Oil

Product Description

Gulfmar MX is marine engine oil developed to meet the performance requirements of modern turbocharged and naturally aspirated marine diesel engines operating on distillate diesel fuel. It is blended from highly refined base stocks and proven performance additives to provide good detergency, dispersancy and antiwear protection with effective acid neutralization capability. The product meets the requirements of most of the medium and high speed marine diesel engines.

Features & Benefits

- High oxidation stability reduces sludge build up & viscosity increase to facilitate long drain intervals
- Improved detergency reduces deposits, keeps engine clean and protects against bore polishing
- Improved dispersancy ensures soot dispersion to control oil thickening and wear
- Good TBN retention ensures effective acid neutralisation
- Effective antiwear properties protect critical engine components to extend engine life and reduce maintenance costs

Applications

- Turbocharged and naturally aspirated 4-stroke medium and high speed marine diesel engines requiring oils meeting the specifications given in the table below.
- Rescue boats, lifeboats, fishing trawlers and coastal vessels.
- Heavy duty diesel engines used in mining, construction, agriculture and other off-highway applications
- Transmissions requiring oil meeting the performance levels given below, more specifically Allison C-4 specifications.
- General ship applications requiring oils meeting the below mentioned specifications

Specifications, Approvals & Typical Properties

Meets the following Specifications		15W-40
API CG-4, SL, SJ		
ACEA E3, E2		
DaimlerChrysler MB 228.3, Volvo VDS-2		
MTU Oil Category 2, MAN M 3275		
Allison C-4		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	14.60
Viscosity Index	D 2270	136
Flash Point, °C	D 92	225
Pour Point, °C	D 97	-30
TBN, mg KOH/g	D 2896	10.49
Density @ 15°C, Kg/l	D 1298	0.895
Sulphated Ash, wt%	D 874	1.46

July 2007

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.