Gulf Formula Extended Performance

Fully Synthetic Passenger Car Motor Oil

Product Description

Gulf Formula Extended Performance series is the most advanced fully synthetic passenger car motor oil developed for modern high-output Turbocharged Gasoline Direct Injection (TGDI) engines in passenger cars, Sports Utility Vehicles (SUVs), vans, and light-duty trucks. It meets the performance requirements of GM gasoline specification dexos1™Gen 3 (SAE 0W-20 only) and highest API SQ (Resource Conserving) & ILSAC GF-7A specifications. These oils offer improved fuel economy and ultimate protection against wear & deposits and address major field concerns as compared to API SP/ILSAC GF-6A oils. It provides advanced protection against Low-Speed Pre-Ignition (LSPI) throughout the oil life and helps prevent timing chain wear issues generally observed in the latest TGDI engines.

Features & Benefits

- Improved fuel economy over previous generation oils
- Advanced protection of TGDI engines against LSPI throughout the oil life and helps prevent timing chain wear
- Excellent shield against engine deposits and wear
- Upgraded chemistry protects against Gasoline Particulate Filter (GPF) deposits & clogging
- Exceptional seal compatibility prevents oil leakage and external contaminants ingress
- Outstanding low temperature fluidity provides wear protection at engine start-up
- Compatible with ethanol-containing fuels up to E85

Application

- Recommended for vehicles requiring GM dexos1 ™Gen 3 type of oils (SAE 0W-20 only)
- High output Turbocharged Gasoline Direct Injection (TGDI) engines in passenger cars, Sports Utility Vehicles (SUVs), Multi-Purpose Vehicles (MPVs), vans, and light-duty trucks of North American, Japanese, Korean OEMs operating on gasoline and ethanol mix fuels up to E85
- Vehicles requiring API SQ/ ILSAC GF-7A, API SP/ILSAC GF-6A or previous generation oils

Specifications, Approvals & Typical Properties

Meets the following Specifications/Suitable for Use		**0W-20**	**5W-20**	**5W-30**
Ford WSS-M2C972-A1, Ford WSS-M2C962-A1		X		
Ford WSS-M2C970-A1, Ford WSS-M2C960-A1			X	
Ford WSS-M2C971-A1, Ford WSS-M2C961-A1				X
Has the following Approvals				
API SQ (Resource Conserving), ILSAC GF-7A		X	X	X
GM dexos1™ Gen 3 (License Numbers: D330BCHG176 / D335BBHG176)		X		
Typical Properties				
Test Parameters	**ASTM Method**	**Typical Values**		
Viscosity @ 100 ºC, cSt	D 445	8.5	8.6	10.0
Viscosity Index	D 2270	163	155	160
Flash Point, ºC	D 92	229	210	205
Pour Point, ºC	D 97	-42	-48	-45
TBN, mg KOH/g	D 2896	7.9	7.2	7.2
Density @ 15ºC, Kg/l	D 1298	0.8450	0.8475	0.8500
Sulfated Ash, %wt	D 874	0.81	0.70	0.70
HTHS, cP	D 4683	2.6	2.70	3.00

Gulf Lubricants Inc., USA, November 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com