



Gulf Formula Advanced

Fully Synthetic Passenger Car Motor Oil

Product Description

Gulf Formula Advanced series is the latest generation fully synthetic passenger car motor oils developed for modern high-output Turbocharged Gasoline Direct Injection (TGDI) engines in passenger cars, Sports Utility Vehicles (SUVs), vans, and light-duty trucks. It meets the highest API SQ (Resource Conserving) & ILSAC GF-7 specifications, addressing major field concerns observed with previous generation oils. It offers improved fuel economy and ultimate protection against wear & deposits as compared to previous generation oils. The low-HTHS SAE 0W-16 formulation meeting ILSAC GF-7B requirements further improves fuel economy as compared with ILSAC GF-7A oils. These oils provide advanced protection against Low-Speed Pre-Ignition (LSPI) throughout the oil life and help prevent timing chain wear issues generally observed in the latest TGDI engines.

Features & Benefits

- Improved fuel economy over previous generation oils
- Advanced protection of TGDI engines against LSPI throughout the oil life and helps prevent timing chain wear
- Excellent shield against engine deposits and wear
- Upgraded chemistry protects against Gasoline Particulate Filter (GPF) deposits & clogging
- Exceptional seal compatibility prevents oil leakage and external contaminants ingress
- Outstanding low temperature fluidity provides wear protection at engine start-up
- Compatible with ethanol-containing fuels up to E85

Applications

- High output Turbocharged Gasoline Direct Injection (TGDI) engines in passenger cars, Sports Utility Vehicles (SUVs), Multi-Purpose Vehicles (MPVs), vans, and light-duty trucks of North American, Japanese, Korean OEMs
- Vehicles requiring API SQ, ILSAC GF-7A/ILSAC GF-7B, API SP, ILSAC GF-6A/ILSAC GF-6B or previous generation oils
- Passenger cars and light-duty vehicles operating on gasoline and ethanol mix fuels up to E85

Specifications, Approvals & Typical Properties

Meets the following Specifications/Suitable for Use		0W-16	0W-20	10W-30
Ford WSS-M2C972-A1, Ford WSS-M2C962-A1			X	
Has the following Approvals				
API SQ (Resource Conserving)		X	X	X
ILSAC GF-7A			X	X
ILSAC GF-7B		X		
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	7.3	8.6	10.0
Viscosity Index	D 2270	160	165	150
Flash Point, °C	D 92	200	205	210
Pour Point, °C	D 97	-51	-45	-42
TBN, mg KOH/g	D 2896	7.2	7.2	7.2
Density @ 15°C, Kg/l	D 1298	0.8440	0.8450	0.8520
Sulfated Ash, %wt	D 874	0.70	0.70	0.70
HTHS, cP	D 4683	2.40	2.70	3.00

Gulf Lubricants Inc., USA, July 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.