



Gulf Harmony HVI

Premium Quality High Viscosity Index Hydraulic Oil for Extreme Temperature Ranges

Product Description

Gulf Harmony HVI series is a premium-quality anti-wear hydraulic oil specially developed for applications operating over a wide temperature range or where small viscosity change with fluctuating temperature is required. They are formulated with high-quality paraffinic base oils, a highly shear-stable polymer and an advanced additive system to meet the stringent requirements of modern hydraulic systems. These oils provide excellent protection against oxidation degradation, rust and corrosion and wear. They also possess superior foam control, water-separation and rapid air-release properties. These oils exceed the performance requirements of global industry standards viz. DIN 51524 Part 3 HVLP, AFNOR NFE 48-603 (HV) & ISO 11158 HV and major international OEMs viz. Hitachi, Eaton & Denison

Features & Benefits

- Exceptional anti-wear property results in longer component life, reducing costs
- Extremely high viscosity index assures equipment protection at cold start-up temperatures and at high operating temperatures
- Excellent shear stability minimises viscosity loss over time and exhibits “stay-in-grade” performance under high shear conditions
- Excellent thermo-oxidative stability controls the formation of sludge and varnish and improves oil life
- Superior demulsibility helps in faster separation of water from oil and resists formation of emulsions
- Special rust and corrosion inhibitors protect multi-metallurgy components even in the presence of moisture
- Rapid air-release property minimises chances of pump cavitation, leading to trouble-free operations
- Compatible with multi-metals & most sealing materials commonly used in hydraulic systems

Application

- Hydraulic and power transmission systems subject to a wide range of ambient and operating temperatures
- Critical high-precision industrial hydraulic systems
- Hydraulic systems of excavators, cranes and hydrostatic drives operating under most severe outdoor conditions

Specifications, Approvals & Typical Properties

ISO Viscosity grades			15	22	32	46	68
Meets the following Specifications							
DIN 51524 Part 3 HVLP, AFNOR NFE 48-603 (HV), ISO 11158 HV			X	X	X	X	X
Denison HF-0, HF-1, HF-2, Eaton (Vickers) M-2950-S, M-2952-S, I-286-S					X	X	X
Bosch Rexroth 07 075 for vane, piston & gear pumps, Sauer Danfoss 520L0463, BR 90220					X	X	X
Typical Properties							
Test Parameters			ASTM Method		Typical Values		
Viscosity @ 40 °C, cSt			D 445		15	22	32 46 68
Viscosity Index			D 2270		152	151	150 152 151
Flash Point, °C			D 92		144	186	218 218 226
Pour Point, °C			D 97		-42	-42	-39 -36 -36
Density @ 15°C, Kg/l			D 1298		0.843	0.868	0.868 0.874 0.881
Rust Test			D 665A/B		Pass	Pass	Pass Pass Pass
Emulsion Test		@ 54°C	D 1401		Pass	Pass	Pass Pass Pass
30 minutes max		@ 82°C			-	-	- - -
Foam Stability in all three sequences, ml			D 892		Nil	Nil	Nil Nil Nil
Turbine Oil Stability Test, hrs			D 943		-	-	2500+
FZG, fail load stage, minimum			DIN 51354 Part II		-	-	11 11 11

Gulf Lubricants Inc., USA, July 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com