



Gulf MAX Ultra+ High Mileage

Synthetic Blend Passenger Car Motor Oil

Product Description

Gulf MAX Ultra+ High Mileage is an advanced synthetic blend passenger car motor oil developed for high-output Turbocharged Gasoline Direct Injection (TGDI) engines in passenger cars, Sports Utility Vehicles (SUVs), vans, and light-duty trucks that have clocked more than 75000 miles. It meets API SQ (Resource Conserving)/ILSAC GF-7A oil specifications and addresses major field concerns observed with previous generation oils. These oils provide advanced protection against Low-Speed Pre-Ignition (LSPI) throughout oil life and prevent timing chain wear issues generally observed in the latest TGDI engines. These oils offer improved fuel economy and excellent protection against wear & deposits compared with API SP/ ILSAC GF-6A oils.

Features & Benefits

- Improved fuel economy over previous generation oils
- Enhanced shield against engine deposits and wear
- Excellent low-temperature fluidity provides wear protection at engine start-up
- Advanced protection of TGDI engines against timing chain wear and LSPI throughout the oil life
- Upgraded chemistry protects against Gasoline Particulate Filter (GPF) deposits & clogging
- Special seal swell agents prevent oil leakage and external contaminants ingress

Applications

- High output Turbocharged Gasoline Direct Injection (TGDI) engines in passenger cars, Sports Utility Vehicles (SUVs), Multi-Purpose Vehicles (MPVs), vans, and light-duty trucks of North American, Japanese & Korean OEMs, especially those which have crossed 75000 miles
- Older Vehicles requiring API SQ/ILSAC GF-7A, API SP/ILSAC GF-6A or previous generation oils
- Passenger cars and light-duty vehicles operating on gasoline and ethanol mix fuels up to E85

Specifications, Approvals & Typical Properties

Has the following Approvals		10W-30
API SQ (Resource Conserving), ILSAC GF-7A		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	10.5
Viscosity Index	D 2270	155
Flash Point, °C	D 92	200
Pour Point, °C	D 97	-36
TBN, mg KOH/g	D 2896	7.2
Density @ 15°C, Kg/l	D 1298	0.8520
Sulfated Ash, %wt	D 874	0.70
HTHS, cP	D 4683	3.0

Gulf Lubricants Inc., USA, July 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.