



Gulf Super Duty CF+ Commercial Vehicle Engine Oil

Product Description

Gulf Super Duty CF+ series are heavy duty diesel engine oils developed to meet the requirements of diesel engines used in various applications, including those operating under severe conditions. These are formulated to provide effective protection for engines running in various environments. Gulf Super Duty CF+ is suitable for use in a wide range of on- and off-highway applications where such type of lubricant is recommended.

Features & Benefits

- Improved detergency helps reduce deposits and keeps engines cleaner
- Better thermo-oxidative stability protects against sludge build-up, deposits & oil degradation and controls oil thickening
- Effective antiwear properties protect engine components against wear to offer extended engine life and reduced maintenance costs
- Good corrosion inhibition properties protect against corrosion and wear

Application

- Turbocharged and naturally aspirated diesel engines of all leading engine manufacturers
- On-highway applications including light and heavy-duty applications
- Heavy-duty diesel engines used in mining, construction, agriculture and other off-highway applications
- SAE 10W and SAE 30 grades are suitable for use in some specific hydraulic and transmission applications, respectively, in various heavy-duty Dumpers, Dozers, Excavators, Tippers and Cranes used in the construction and mining industry where such type of oil is recommended

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W	30	40	50
API CF-2			X	X	X
API CF/ SG		X	X	X	X
Caterpillar TO-2, Allison C3/C4		X	X	X	X
Typical Properties					
Test Parameters	ASTM	Typical Values			
Viscosity @ 100 °C, cSt	D 445	6.5	11.7	15.5	18.7
Viscosity Index	D 2270	135	94	112	110
Flash Point, °C	D 92	236	252	250	260
Pour Point, °C	D 97	-42	-39	-30	-24
TBN, mg KOH/g	D 2896	8.5	8.5	8.5	8.5
Density @ 15°C, Kg/l	D 1298	0.8532	0.8680	0.8770	0.8810

Gulf Lubricants Inc., USA, July 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com