



Gulf Syngear HP

High-Performance Synthetic Gear Oil

Product Description

Gulf Syngear HP series is a fully synthetic, thermally stable axle lubricant designed to meet the demanding requirements of heavy-duty commercial vehicles and off-highway equipment operating in most severe and varying load conditions. It offers unmatched protection for extended durability of driveline components. These oils, possessing outstanding load-carrying capability and high viscosity index, provide effective lubrication in applications encountering high-speed/shock load and/or low-speed/high torque conditions and wide temperature ranges.

Features & Benefits

- Provides outstanding load-bearing characteristics resulting in longer gear and bearing life and leading to reduced maintenance costs and increased vehicle uptime.
- Exceptional thermo-oxidative stability helps in keeping the gear clean for longer periods and extending the oil life – significantly longer than conventional gear oils
- Effective rust and corrosion protection, especially to copper and its alloys, reduces wear, extends synchroniser life and improves shifting performance
- Outstanding low temperature fluidity reduces wear at start-up even under low ambient temperatures
- Exceptional shear stability helps in retaining viscosity and film strength to protect against wear even under severe operating conditions

Applications

- Heavy-duty on-highway vehicles and off-highway equipment transmissions, transfer cases, axles and final drives where API GL-5, API MT-1, MIL-PRF-2105E or SAE J 2360 quality oils are specified
- It satisfies most of the Limited Slip requirements for North American Heavy Duty equipment manufacturers. In case of any specific or higher Limited Slip requirements, please contact your local Gulf Representative.
- Not recommended for automatic transmissions

Specifications, Approvals & Typical Properties

Meets the following Specifications		75W-90	80W-140
API GL-5, API MT-1, MIL-PRF-2105E, SAE J 2360		X	X
Mack GO-J, DANA SHAES 256 Rev C		X	X
Meritor O-76N, O-76E		X	
Meritor O-76B			X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity at 100 °C, cSt	D 445	16.3	26.5
Viscosity Index	D 2270	176	161
Flash Point, °C	D 92	218	214
Brookfield, cP	D 2983	78,000 @ -40°C	40,000@ -26°C
Pour Point, °C	D 97	-40	-34
Density @ 15°C, kg/l	D 1298	0.8540	0.8515

Gulf Lubricants Inc., USA, July 2026

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.