



Gulf ATF DX III

High-Performance Automatic Transmission Fluid

Product Description

Gulf ATF DX III is a high-performance automatic transmission fluid for General Motors and Ford automatic transmissions requiring dexronTM IIIH or MERCON[®] quality fluids, respectively. It provides enhanced transmission & oil protection through superior thermo-oxidative stability, corrosion & rust protection, foam control, seal compatibility, friction durability and low-temperature fluidity. It is designed to meet the performance requirements of General Motors dexronTM IIIH and Ford MERCON[®] specifications.

Features & Benefits

- Superior thermo-oxidative stability, wear protection and resistance to chemical degradation provide longer fluid and component life
- Controlled frictional properties lead to smooth shift performance, efficient transmission of power and prevent shudder
- Extremely high viscosity index ensures adequate lubrication in both high operating & cold-start conditions
- Provides excellent protection against rust and corrosion
- Effective foam control leads to smooth & consistent shift performance and reduces fluid loss
- Improved low temperature fluidity leads to easy pumping in the hydraulic circuits
- Better seal compatibility ensures longer seal life and reduces the possibility of oil leakage

Application

- Recommended for vehicles of General Motors requiring dexronTM IIIH and Ford requiring MERCON[®] quality fluids.
- Being backwards compatible, also suitable for automatic transmissions requiring General Motors dexronTM III, dexronTM IIE or dexronTM IID fluids or in other applications where such fluids are specified

Specifications, Approvals & Typical Properties

Meets the following Specifications/Suitable for Use		
GM dexron TM IIIH/IIIG		
Ford MERCON [®] , Allison C-4		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	7.2
Viscosity Index	D 2270	170
Flash Point, °C	D 92	190
Pour Point, °C	D 97	-48
Brookfield Viscosity @ -40°C, cP	D 2983	12000
Density @ 15°C, Kg/l	D 1298	0.8500

Gulf Lubricants Inc., USA, August 2026

dexronTM is a trademark of General Motors Corporation
MERCON[®] is a registered trademark of Ford Motor Company

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com